


Monteringsstik

Varenr. 3531




- skrueterminaler
- med beskyttelseslåg

Tekniske data

Ampere	16 A
Poler	3 p
Volt	230 V
Klokposition	6 h
Hertz	50-60 Hz
Forbindelsesteknologi	Skruekontakt
Kontakt	standard
Beskyttelsestype	IP67
Vægt	212 g
Overensstemmelseserklæring	VDE, EAC

Dimensioner



Drawing	Amp.	16			32			63		
		Poles			3	4	5	3	4	5
2 MB 62										
Dim. in mm		a	b	c	d	e	f	g	g.1	h
		85	85	85	85	85	108	108	108	101
		132	132	131	131	137	164	164	164	101
		70	70	70	70	70	85	85	85	77
		70	70	70	70	70	77	77	77	12
		6.3	6.3	6.3	6.3	6.3	6.5	6.5	6.5	2
		11	11	11	11	11	12	12	12	100
		2	2	2	2	2	2	2	2	70
		100	107	108	108	111	130	130	130	87
		70	87	94	94	102	114	114	114	30
		30	30	30	30	30	40	40	40	1
Terminal for cond. cross section (mm ²) min.-max.		1	1	2,5	2,5	2,5	6	6	6	-2,5
				-2,5	-2,5	-6	-6	-6	-16	-16
										-16